## NSN 5306-01-414-5627

Shear Bolt - Page 1 of 2

Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/5306-01-414-5627 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.454 inches **Fastener Length:** Between 3.064 inches and 3.094 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 2.615 inches and 2.635 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Minimum Yield Strength: 95000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq0-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

## NSN 5306-01-414-5627

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0