## NSN 5306-01-414-6635

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-414-6635

| TI 101  |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:                                       |
| Right-hand  |
| Thread Length:  |
| 0.780 inches  |
| Fastener Length:  |
| 1.968 inches  |
| Head Style:   |
| Spline extended washer                                  |
| Head Height:  |
| Between 0.440 inches and 0.460 inches                   |
| Extended Washer Diameter:                               |
| Between 0.922 inches and 0.932 inches                   |
| Extended Washer Thickness:                              |
| Between 0.062 inches and 0.082 inches                   |
| Grip Diameter:  |
| Between 0.4990 inches and 0.4995 inches                 |
| Head Minor Diameter:                                    |
| 0.644 inches  |
| Thread Diameter:  |
| 0.500 inches  |
| Grip Length:  |
| 1.188 inches  |
| Thready Qty Per Inch (tpi):                             |
| 20  |
| Min. Tensile Strength (psi):                            |
| 220000 pounds per square inch                           |
| Surface Finish:   |
| 32.0 microinches threads                                |
| Material:   |
| Nickel alloy 718  |
| Material Specification:                                 |
| Ams 5662 federal specification single material response |
| Surface Treatment:                                      |
| Passivate   |
| Surface Treatment Specification:                        |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator:                               |
| Unjf  |
| Shelf Life:   |
| N/a   |

## NSN 5306-01-414-6635

Shear Bolt - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A003b0