NSN 5306-01-416-3033



Externally Relieved Body Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-416-3033 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.990 inches **Fastener Length:** 1.125 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.422 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** 0.562 inches **Extended Washer Thickness:** Between 0.090 inches and 0.100 inches **First Diameter From Head:** Between 0.343 inches and 0.353 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.125 inches and 0.145 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 42.0 rockwell c and 46.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 601 **Material Specification:** Ams 6304 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-416-3033

Externally Relieved Body Bolt - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0