## NSN 5306-01-416-5242

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-416-5242

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.520 inches
Fastener Length:
Between 1.020 inches and 1.050 inches
Head Style:
Spline extended washer
Head Height:
Between 0.240 inches and 0.260 inches
Extended Washer Diameter:
Between 0.460 inches and 0.470 inches
Extended Washer Thickness:
Between 0.026 inches and 0.046 inches
Hole Diameter:
Between 0.032 inches and 0.042 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Head Minor Diameter:
Between 0.235 inches and 0.250 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
260000 pounds per square inch
Hardness Rating:
51.0 rockwell c and 54.0 rockwell c
Hole Configuration Style:
Round longitudinal hole
Surface Finish:
32.0 microinches grip
Material:
Steel comp h11

## NSN 5306-01-416-5242

Shear Bolt - Page 2 of 2

A003b0

Mil-c-8837 spec.

Mil-std (military Standard):



Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837, type 2, class 2 military specification all treatment responses
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: