NSN 5306-01-416-7217

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-416-7217 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.071 inches and 0.851 inches **Fastener Length:** 2.000 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.303 inches Width Between Flats: 0.3125 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** 0.060 inches **First Diameter From Head:** Between 0.222 inches and 0.232 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.190 inches and 1.250 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** 32 surface finish on bearing surface of head, grip, and threads Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response

Unjf

Thread Series Designator:

NSN 5306-01-416-7217

Externally Relieved Body Bolt - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0