

View Online at <https://aerobasegroup.com/nsn/5306-01-416-7217>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.071 inches and 0.851 inches

**Fastener Length:**

2.000 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.303 inches

**Width Between Flats:**

0.3125 inches

**Extended Washer Diameter:**

0.438 inches

**Extended Washer Thickness:**

0.060 inches

**First Diameter From Head:**

Between 0.222 inches and 0.232 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 1.190 inches and 1.250 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

32 surface finish on bearing surface of head, grip, and threads

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0