NSN 5306-01-417-3084

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-417-3084

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.455 inches |
| Fastener Length: |
| 4.970 inches |
| Head Style: |
| Spline extended washer |
| Head Height: |
| Between 0.240 inches and 0.260 inches |
| Extended Washer Diameter: |
| Between 0.460 inches and 0.470 inches |
| Extended Washer Thickness: |
| Between 0.026 inches and 0.046 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Head Minor Diameter: |
| Between 0.235 inches and 0.250 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 4.490 inches and 4.510 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 39.0 rockwell c and 43.0 rockwell c |
| Material: |
| Steel comp 4140 or steel comp 6150 or steel comp 8740 |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, ty2cl3 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 96906-ms21134-04072 government standard |
| Shelf Life: |
| |

N/a

NSN 5306-01-417-3084

Shear Bolt - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A003b0