

View Online at <https://aerobasegroup.com/nsn/5306-01-417-7315>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.578 inches

Fastener Length:

Between 2.438 inches and 2.468 inches

Head Style:

Dished hexagon

Head Height:

Between 0.188 inches and 0.193 inches

Width Between Flats:

0.623 inches

Grip Diameter:

0.523 inches

Shank Unthreaded Hole Diameter:

0.106 inches and 0.116 inches threads

Thread Diameter:

0.3750 inches

Grip Length:

Between 1.865 inches and 1.885 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Minimum Yield Strength:

95000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.358 inches and 2.378 inches threads

Surface Finish:

32.0 microinches threads

Material:

Stainless steel

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6706 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0