NSN 5306-01-417-9027

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-417-9027

3a
Thread Direction:
Right-hand
Thread Length:
1.348 inches
Fastener Length:
Between 4.035 inches and 4.065 inches
Head Style:
Spline extended washer
Head Height:
Between 0.069 inches and 0.710 inches
Extended Washer Diameter:
Between 1.615 inches and 1.625 inches
Extended Washer Thickness:
Between 0.116 inches and 0.136 inches
Grip Diameter:
Between 0.8730 inches and 0.8740 inches
Head Minor Diameter:
Between 0.923 inches and 0.938 inches
Thread Diameter:
0.875 inches
Grip Length:
Between 1.678 inches and 1.698 inches
Thready Qty Per Inch (tpi):
14
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837, type 2, class 2, military specification all treatment responses
Thread Series Designator:
Unif

NSN 5306-01-417-9027

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Shelf Life:

Mil-std (military Standard): Mil-c-8837 spec.