NSN 5306-01-419-4491

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-419-4491

Thread Direction: Right-hand Thread Length: 0.997 inches Fastener Length: Between 2.607 inches and 2.637 inches Head Style: Spline extended washer Head Height: Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter: Between 0.711 inches and 0.717 inches
Right-hand Thread Length: 0.997 inches Fastener Length: Between 2.607 inches and 2.637 inches Head Style: Spline extended washer Head Height: Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Thread Length: 0.997 inches Fastener Length: Between 2.607 inches and 2.637 inches Head Style: Spline extended washer Head Height: Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
0.997 inches Fastener Length: Between 2.607 inches and 2.637 inches Head Style: Spline extended washer Head Height: Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Fastener Length: Between 2.607 inches and 2.637 inches Head Style: Spline extended washer Head Height: Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Between 2.607 inches and 2.637 inches Head Style: Spline extended washer Head Height: Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Head Style: Spline extended washer Head Height: Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Spline extended washer Head Height: Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Head Height: Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Between 0.410 inches and 0.450 inches Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Extended Washer Diameter: Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Between 1.037 inches and 1.047 inches Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Extended Washer Thickness: Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Between 0.071 inches and 0.091 inches Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Grip Diameter: Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Between 0.5605 inches and 0.5615 inches Head Minor Diameter:
Head Minor Diameter:
Between 0.711 inches and 0.717 inches
Thread Diameter:
0.562 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches grip
Special Features:
On.75 (-12) and larger, center drilling of shank is optional
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5306-01-419-4491

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0