NSN 5306-01-419-4679

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-419-4679

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.938 inches |
| Fastener Length: |
| 6.000 inches |
| Head Style: |
| Flat fillister |
| Head Diameter: |
| Between 0.850 inches and 1.000 inches |
| Head Height: |
| 0.268 inches |
| Hole Diameter: |
| 0.070 inches |
| Grip Diameter: |
| Between 0.6200 inches and 0.6240 inches |
| Thread Diameter: |
| 0.625 inches |
| Grip Length: |
| 5.062 inches |
| Hole Quantity: |
| 6 |
| Ноје Туре: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, tyii, cl2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| |

80205-nas150 professional/industrial association standard

NSN 5306-01-419-4679

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

