
NSN 5306-01-419-5160

Shear Bolt - Page 1 of 2



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 1.009 inches Fastener Length: Between 2.806 inches and 2.836 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.701 inches and 0.721 inches Width Between Flats: Between 0.803 inches and 0.814 inches **Extended Washer Diameter:** Between 1.220 inches and 1.230 inches **Extended Washer Thickness:** 0.178 inches Grip Diameter: Between 0.7485 inches and 0.7490 inches Single Shear Strength: 125000 pounds per square inch **Thread Diameter:** 0.750 inches Grip Length: Between 1.802 inches and 1.822 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches grip **Product Name:** Navy special project Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:**



Qq-p-35 federal specification single treatment response

NSN 5306-01-419-5160

Shear Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

