NSN 5306-01-419-6027

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-419-6027 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.495 inches **Fastener Length:** Between 1.433 inches and 1.463 inches **Head Style:** Spline extended washer **Head Height:** Between 0.240 inches and 0.260 inches **Extended Washer Diameter:** Between 0.460 inches and 0.470 inches **Extended Washer Thickness:** Between 0.026 inches and 0.045 inches **Hole Diameter:** Between 0.032 inches and 0.042 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Head Minor Diameter:** Between 0.318 inches and 0.324 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.937 inches and 0.948 inches **Hole Quantity:** Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Hole Configuration Style:** Spline Material:

Steel

NSN 5306-01-419-6027

Shear Bolt - Page 2 of 2

A003b0

Mil-c-8837 spec.

Mil-std (military Standard):



Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: