

View Online at <https://aerobasegroup.com/nsn/5306-01-420-3600>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.670 inches

Fastener Length:

Between 3.238 inches and 3.258 inches

Head Style:

Hexagon

Head Height:

Between 0.251 inches and 0.266 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.4986 inches and 0.4991 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

Between 2.562 inches and 2.578 inches

Thready Qty Per Inch (tpi):

20

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.126 inches first hole

Special Features:

Spindle and pawl material: ph13-8mo or 17-4ph. Plug material: cres type 303. Ball material: cres type 440c

Material:

Nickel alloy 718 fastener

Material Specification:

Ams 5662 assn standard single material response fastener

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0