NSN 5306-01-420-8875

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-420-8875 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.531 inches and 1.625 inches **Fastener Length:** Between 2.156 inches and 2.250 inches **Head Style:** Hexagon **Head Height:** Between 0.455 inches and 0.483 inches Width Between Flats: Between 1.100 inches and 1.125 inches **First Diameter From Head:** 0.625 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.625 inches **Thread Diameter:** 0.750 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 70000 pounds per square inch **Hardness Rating:** 40.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch **Externally Relieved Body Diameter Quantity: Special Features:** Altered from ms35307-488, nsn 5305012736459 Material: Steel **Material Specification:** Fed 66, 300 series federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5306-01-420-8875

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0