

View Online at <https://aerobasegroup.com/nsn/5306-01-420-8875>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.531 inches and 1.625 inches

Fastener Length:

Between 2.156 inches and 2.250 inches

Head Style:

Hexagon

Head Height:

Between 0.455 inches and 0.483 inches

Width Between Flats:

Between 1.100 inches and 1.125 inches

First Diameter From Head:

0.625 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.625 inches

Thread Diameter:

0.750 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

10

Min. Tensile Strength (psi):

70000 pounds per square inch

Hardness Rating:

40.0 rockwell c

Minimum Yield Strength:

30000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Special Features:

Altered from ms35307-488, nsn 5305012736459

Material:

Steel

Material Specification:

Fed 66, 300 series federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0