

View Online at <https://aerobasegroup.com/nsn/5306-01-420-9832>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.385 inches

Fastener Length:

1.030 inches

Head Style:

Double hexagon w/hole

Head Height:

0.250 inches

Width Between Flats:

0.219 inches

Extended Washer Diameter:

Between 0.290 inches and 0.300 inches

Extended Washer Thickness:

0.050 inches

Hole Diameter:

Between 0.032 inches and 0.042 inches

Grip Diameter:

Between 0.1625 inches and 0.1635 inches

Thread Diameter:

0.164 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Hole Configuration Style:

Round longitudinal hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-85038503 military specification 4th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.