

View Online at <https://aerobasegroup.com/nsn/5306-01-421-2052>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.528 inches

Fastener Length:

Between 2.138 inches and 2.168 inches

Head Style:

Dished hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Single Shear Strength:

95000 pounds per square inch

Thread Diameter:

0.500 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6208 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.