

View Online at <https://aerobasegroup.com/nsn/5306-01-421-5067>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.543 inches

Fastener Length:

Between 2.340 inches and 2.360 inches

Head Style:

Hexagon

Head Height:

Between 0.312 inches and 0.327 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Hole Diameter:

Between 0.060 inches and 0.080 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 1.802 inches and 1.822 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Hexagon corners

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 5622 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.