NSN 5306-01-421-5067

View Online at https://aerobasegroup.com/nsn/5306-01-421-5067

Shear Bolt - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.543 inches **Fastener Length:** Between 2.340 inches and 2.360 inches **Head Style:** Hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Hole Diameter:** Between 0.060 inches and 0.080 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Thread Diameter:** 0.625 inches

Grip Length:

Between 1.802 inches and 1.822 inches

Hole Quantity:

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Hexagon corners

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 5622 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

NSN 5306-01-421-5067

Shear Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Shelf Life:

Mil-std (military Standard):

Mil-s-5000 spec.

A003b0