

View Online at <https://aerobasegroup.com/nsn/5306-01-422-0739>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.572 inches

Fastener Length:

Between 2.251 inches and 2.281 inches

Head Style:

Dished hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Locking Feature:

Patch threads or strip threads

Grip Diameter:

Between 0.3731 inches and 0.3737 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.678 inches and 1.698 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4340 fastener or steel comp 8740 fastener

Material Specification:

Mil-s-5000 military specification 1st material response fastener or mil-s-6049 military specification 2nd material response fastener or ams 6322 assn standard 2nd material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses locking feature

Thread Series Designator:

Unjf

Specification Data:

80205-nas6606 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.