

View Online at <https://aerobasegroup.com/nsn/5306-01-422-9310>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.896 inches

Fastener Length:

Between 3.896 inches and 3.926 inches

Head Style:

Spline extended washer

Head Height:

Between 1.190 inches and 1.210 inches

Extended Washer Diameter:

Between 2.770 inches and 2.780 inches

Extended Washer Thickness:

Between 0.206 inches and 0.225 inches

Grip Diameter:

Between 1.4975 inches and 1.4990 inches

Head Minor Diameter:

Between 1.610 inches and 1.625 inches

Thread Diameter:

1.500 inches

Grip Length:

Between 1.990 inches and 2.010 inches

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp 4140 or steel comp 4340 or steel comp 6150 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.