

View Online at <https://aerobasegroup.com/nsn/5306-01-423-0891>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.578 inches

Fastener Length:

2.703 inches

Head Style:

Dished hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Washer Quantity:

1

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Minimum Yield Strength:

95000 pounds per square inch

Primary Washer Outside Diameter:

0.600 inches

Primary Washer Style:

Spring tension

Primary Washer Material Thickness:

0.032 inches

Special Features:

FURN-IS-HED-WITH

Material:

Steel comp 303se stand-off

Material Specification:

Mil-s-5000, cond a military specification single material response first shoulder

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.