

View Online at <https://aerobasegroup.com/nsn/5306-01-423-1430>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.444 inches

**Fastener Length:**

1.734 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.109 inches and 0.141 inches

**Width Between Flats:**

Between 0.367 inches and 0.377 inches

**Shoulder Diameter:**

0.2494 inches first shoulder and 0.2505 inches first shoulder

**Shoulder Length:**

1.290 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole

**End Application:**

F-16

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.584 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard 1st material response or ams 6487 assn standard 2nd material response

**Surface Treatment:**

Cadmium head

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response threads

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0