## NSN 5306-01-423-2038

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-423-2038

| Thread Direction:  |
|--|
| Right-hand   |
| Thread Length:   |
| Between 13.1 millimeters and 16.4 millimeters                            |
| Fastener Length:   |
| Between 15.60 millimeters and 16.40 millimeters                          |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 5.1 millimeters and 5.5 millimeters                              |
| Width Between Flats:   |
| Between 12.7 millimeters and 13.0 millimeters                            |
| Thread Diameter:   |
| 8.0 millimeters  |
| Features Provided:   |
| Finished head  |
| Min. Tensile Strength (psi):   |
| 1040 megapascals   |
| Hardness Rating:   |
| 33.0 rockwell c and 39.0 rockwell c                                      |
| Minimum Yield Strength:  |
| 940 megapascals  |
| Thread Pitch In Millimeters:   |
| 1.25   |
| External Thread Tolerance Class:   |
| 6g   |
| Material:  |
| Steel property class 10.9  |
| Material Specification:  |
| Ansi b18.2.3.1m, property cl 10.9 assn standard single material response |
| Surface Treatment:   |
| Zinc and chromate  |
| Surface Treatment Specification:   |
| Qq-z-325, type 2, cl 3 federal specification single treatment response   |
| Thread Series Designator:  |
| М  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
|  |

## **NSN 5306-01-423-2038** Machine Bolt - Page 2 of 2

Fiig: A003b0

