NSN 5306-01-424-7942

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-424-7942
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.041 inches
Fastener Length:
Between 1.776 inches and 1.806 inches
Head Style:
Dished hexagon
Head Height:
Between 0.375 inches and 0.390 inches
Width Between Flats:
Between 1.052 inches and 1.065 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Hole Quantity:
3
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
3rd material response
Surface Treatment:

Cadmium and chromate

NSN 5306-01-424-7942

Shear Bolt - Page 2 of 2



Surface	Treatment	Specification:
---------	------------------	----------------

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.