## NSN 5306-01-424-9556

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand

Thread Length:
1.414 inches

**Thread Direction:** 

Fastener Length:

**Head Style:** 

Between 2.649 inches and 2.679 inches

За



View Online at https://aerobasegroup.com/nsn/5306-01-424-9556

Spline extended washer
Head Height:
0.700 inches
Extended Washer Diameter:
Between 1.615 inches and 1.625 inches
Extended Washer Thickness:
0.120 inches
Grip Diameter:
Between 0.8730 inches and 0.8740 inches
Head Minor Diameter:
Between 0.923 inches and 0.938 inches
Thread Diameter:
0.875 inches
Grip Length:
1.250 inches
Thready Qty Per Inch (tpi):
14
Min. Tensile Strength (psi):
220000 pounds per square inch
Minimum Yield Strength:
125000 pounds per square inch
Surface Finish:
32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-424-9556

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0