## NSN 5306-01-425-2428

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-425-2428 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** Between 2.563 inches and 2.593 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.990 inches and 2.010 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Minimum Yield Strength: 95000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** A, s 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas 4006 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-01-425-2428

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0