## NSN 5306-01-425-6225

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand **Thread Length:**0.813 inches

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-425-6225

Fastener Length:						
Between 3.835 inches and 3.865 inches						
Head Style:						
Double hexagon extended washer						
Head Height:						
Between 0.420 inches and 0.430 inches						
Width Between Flats:						
Between 0.637 inches and 0.651 inches						
Extended Washer Diameter:						
Between 0.818 inches and 0.838 inches						
Extended Washer Thickness:						
Between 0.113 inches and 0.133 inches						
Grip Diameter:						
Between 0.4985 inches and 0.4995 inches						
Single Shear Strength:						
125000 pounds per square inch						
Thread Diameter:						
0.500 inches						
Grip Length:						
Between 2.927 inches and 2.947 inches						
Thready Qty Per Inch (tpi):						
20						
Min. Tensile Strength (psi):						
220000 pounds per square inch						
Surface Finish:						
32.0 microinches threads						
Material:						
Nickel alloy 718						
Material Specification:						
Ams 5662 assn standard single material response						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416, ty2 federal specification 1st treatment response						
Thread Series Designator:						
Unjf						

## NSN 5306-01-425-6225

Shear Bolt - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0