

View Online at <https://aerobasegroup.com/nsn/5306-01-426-7542>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.250 inches

**Fastener Length:**

Between 2.440 inches and 2.500 inches

**Head Style:**

Distorted head

**Head Height:**

Between 0.312 inches and 0.327 inches

**Width Between Flats:**

Between 0.798 inches and 0.812 inches

**Locking Feature:**

Distortions head

**Thread Diameter:**

0.500 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

13

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Minimum Yield Strength:**

120000 pounds per square inch

**Material:**

Steel

**Material Specification:**

J429 grade 8 assn standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-p-16232 ty z cl 2 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-p-16232 spec.