NSN 5306-01-429-1032

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-429-1032 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.538 inches **Fastener Length:** Between 0.961 inches and 0.991 inches **Head Style:** Spline extended washer **Head Height:** Between 0.302 inches and 0.322 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.051 inches and 0.071 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.081 inches first hole **Head Minor Diameter:** Between 0.360 inches and 0.375 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-429-1032

Shear Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0