## NSN 5306-01-429-6601

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-429-6601 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.267 inches and 0.287 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.115 inches Width Between Flats: Between 0.305 inches and 0.313 inches **First Diameter From Head:** Between 0.114 inches and 0.124 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.473 inches **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** F-200, cage 60854 mfr ref single treatment response or mil-std-808 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0

## NSN 5306-01-429-6601

Externally Relieved Body Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-std-808 spec.