

View Online at <https://aerobasegroup.com/nsn/5306-01-432-0359>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.005 inches

Fastener Length:

15.693 inches

Head Style:

Double hexagon w/hole

Head Height:

0.563 inches

Width Between Flats:

Between 0.673 inches and 0.688 inches

Extended Washer Diameter:

Between 1.153 inches and 1.163 inches

Extended Washer Thickness:

Between 0.080 inches and 0.100 inches

Washer Quantity:

1

End Application:

Bolt assembly used on 16s1700 pylon parts assembly-weapon wing f-16 acft

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

18

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Primary Washer Outside Diameter:

Between 1.182 inches and 1.192 inches

Primary Washer Style:

Flat

Primary Washer Material Thickness:

Between 0.071 inches and 0.085 inches

Special Features:

Item is made up of spacer-part number 965548-01, washer-part numberms21299c10 and bolt-part number 965572-01

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.