

View Online at <https://aerobasegroup.com/nsn/5306-01-432-0359>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.005 inches

**Fastener Length:**

15.693 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.563 inches

**Width Between Flats:**

Between 0.673 inches and 0.688 inches

**Extended Washer Diameter:**

Between 1.153 inches and 1.163 inches

**Extended Washer Thickness:**

Between 0.080 inches and 0.100 inches

**Washer Quantity:**

1

**End Application:**

Bolt assembly used on 16s1700 pylon parts assembly-weapon wing f-16 acft

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Primary Washer Outside Diameter:**

Between 1.182 inches and 1.192 inches

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

Between 0.071 inches and 0.085 inches

**Special Features:**

Item is made up of spacer-part number 965548-01, washer-part numberms21299c10 and bolt-part number 965572-01

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.