NSN 5306-01-432-3256

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-432-3256

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.370 inches |
| Fastener Length: |
| Between 4.355 inches and 4.385 inches |
| Head Style: |
| Flat countersunk undercut |
| Head Diameter: |
| 0.508 inches |
| Head Height: |
| 0.111 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 3.990 inches and 4.010 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams4928 assn standard 1st material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, ty2cl2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas4604-64 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5306-01-432-3256

Close Tolerance Bolt - Page 2 of 2

Fiig: A003b0

