## NSN 5306-01-432-5624

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-432-5624 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.813 inches **Fastener Length:** Between 1.287 inches and 1.327 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.420 inches and 0.440 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches **Grip Diameter:** Between 0.5297 inches and 0.5307 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.826 inches and 0.846 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5306-01-432-5624

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0