## NSN 5306-01-432-8662

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand **Thread Length:**0.575 inches

**Thread Direction:** 

Fastener Length:

Spline extended washer

**Head Style:** 

**Head Height:** 

Between 1.623 inches and 1.653 inches

За



View Online at https://aerobasegroup.com/nsn/5306-01-432-8662

Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Head Minor Diameter:
Between 0.360 inches and 0.375 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.063 inches and 1.073 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Minimum Yield Strength:
125000 pounds per square inch
Surface Finish:
32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-432-8662

Shear Bolt - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0