

View Online at <https://aerobasegroup.com/nsn/5306-01-433-5833>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.467 inches

**Fastener Length:**

Between 1.701 inches and 1.748 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.147 inches and 0.167 inches

**Width Between Flats:**

0.502 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.078 inches first hole and 0.081 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 1.240 inches and 1.260 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.603 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A003b0