NSN 5306-01-433-5834

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-433-5834

| Thread Class: |
|--|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.397 inches |
| Fastener Length: |
| Between 2.236 inches and 2.249 inches |
| Head Style: |
| Double hexagon |
| Head Height: |
| Between 0.154 inches and 0.174 inches |
| Width Between Flats: |
| 0.439 inches |
| Grip Diameter: |
| Between 0.2480 inches and 0.2495 inches |
| Shank Unthreaded Hole Diameter: |
| 0.076 inches first hole and 0.081 inches first hole |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 1.177 inches and 1.197 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 2.125 inches first hole and 2.138 inches first hole |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| |

NSN 5306-01-433-5834

Close Tolerance Bolt - Page 2 of 2

Fiig: A003b0

