

View Online at <https://aerobasegroup.com/nsn/5306-01-433-9772>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.715 inches and 0.775 inches

**Shank Length:**

Between 0.715 inches and 0.775 inches

**Eye Stock Diameter:**

0.688 inches

**Shoulder Diameter:**

Between 0.554 inches and 0.559 inches

**Shoulder Length:**

Between 1.740 inches and 1.760 inches

**Ring Stock Diameter:**

Between 0.355 inches and 0.395 inches

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Special Features:**

Threads undercut for relief

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response

**Surface Treatment:**

Cadmium and chromate or zinc and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification 1st treatment response or qq-z-325 type 2 cl 3 federal specification 2nd treatment response

**Style Designator:**

Swivel

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.