NSN 5306-01-435-1735

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-435-1735

80205-nas6305 professional/industrial association standard

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.438 inches
Fastener Length:
Between 1.048 inches and 1.078 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Shoulder Diameter:
0.342 inches all shoulders and 0.343 inches all shoulders
Shoulder Length:
0.615 inches all shoulders and 0.635 inches all shoulders
Thread Diameter:
0.312 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Minimum Yield Strength:
95000 pounds per square inch
Shoulder Shape:
Round all shoulders
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

NSN 5306-01-435-1735

Shoulder Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0