## NSN 5306-01-435-4803

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-435-4803

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.694 inches
Fastener Length:
Between 1.741 inches and 1.771 inches
Head Style:
Dished hexagon
Head Height:
Between 0.219 inches and 0.234 inches
Width Between Flats:
Between 0.678 inches and 0.690 inches
Grip Diameter:
Between 0.4365 inches and 0.4370 inches
Thread Diameter:
0.437 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
Min. Tensile Strength (psi):  160000 pounds per square inch
,
160000 pounds per square inch
160000 pounds per square inch  Minimum Yield Strength:
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch  Surface Finish:
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch  Surface Finish: 32.0 microinches threads
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch  Surface Finish: 32.0 microinches threads  Material:
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch  Surface Finish: 32.0 microinches threads  Material:  Titanium alloy uns r56400
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch  Surface Finish: 32.0 microinches threads  Material:  Titanium alloy uns r56400  Material Specification:
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch  Surface Finish: 32.0 microinches threads  Material:  Titanium alloy uns r56400  Material Specification:  Ams 4928 assn standard single material response or ams 4967 assn standard single material response
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch  Surface Finish: 32.0 microinches threads  Material:  Titanium alloy uns r56400  Material Specification:  Ams 4928 assn standard single material response or ams 4967 assn standard single material response  Thread Series Designator:
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch  Surface Finish: 32.0 microinches threads  Material:  Titanium alloy uns r56400  Material Specification:  Ams 4928 assn standard single material response or ams 4967 assn standard single material response  Thread Series Designator:  Unjf
160000 pounds per square inch  Minimum Yield Strength: 95000 pounds per square inch  Surface Finish: 32.0 microinches threads  Material: Titanium alloy uns r56400  Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response  Thread Series Designator: Unjf  Specification Data:
160000 pounds per square inch Minimum Yield Strength: 95000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas6807 professional/industrial association standard

--

## NSN 5306-01-435-4803

Shear Bolt - Page 2 of 2



em			

No

Fiig:

A003b0