## NSN 5306-01-435-5262

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-435-5262

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.911 inches
Fastener Length:
Between 2.146 inches and 2.176 inches
Head Style:
Spline extended washer
Head Height:
Between 0.495 inches and 0.515 inches
Extended Washer Diameter:
Between 1.037 inches and 1.047 inches
Extended Washer Thickness:
Between 0.051 inches and 0.061 inches
Grip Diameter:
Between 0.5605 inches and 0.5615 inches
Head Minor Diameter:
Between 0.711 inches and 0.717 inches
Thread Diameter:
0.562 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
180000 pounds per square inch
Minimum Yield Strength:
108000 pounds per square inch
Surface Finish:
32.0 microinches grip
Special Features:
Flat countersunk drilling of shank diameter 0.187in. Max.
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response

Surface Treatment: Passivate

## NSN 5306-01-435-5262

Machine Bolt - Page 2 of 2



Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0