NSN 5306-01-435-5262

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-435-5262

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.911 inches |
| Fastener Length: |
| Between 2.146 inches and 2.176 inches |
| Head Style: |
| Spline extended washer |
| Head Height: |
| Between 0.495 inches and 0.515 inches |
| Extended Washer Diameter: |
| Between 1.037 inches and 1.047 inches |
| Extended Washer Thickness: |
| Between 0.051 inches and 0.061 inches |
| Grip Diameter: |
| Between 0.5605 inches and 0.5615 inches |
| Head Minor Diameter: |
| Between 0.711 inches and 0.717 inches |
| Thread Diameter: |
| 0.562 inches |
| Grip Length: |
| Between 1.240 inches and 1.260 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Minimum Yield Strength: |
| 108000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches grip |
| Special Features: |
| Flat countersunk drilling of shank diameter 0.187in. Max. |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |

Surface Treatment: Passivate

NSN 5306-01-435-5262

Machine Bolt - Page 2 of 2



Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0