

View Online at <https://aerobasegroup.com/nsn/5306-01-435-6430>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.968 inches

**Fastener Length:**

Between 2.796 inches and 2.843 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.922 inches and 0.954 inches

**Width Between Flats:**

Between 0.928 inches and 0.939 inches

**Hole Diameter:**

0.070 inches

**Grip Diameter:**

Between 0.620 inches and 0.624 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

1.812 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

11

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon longitudinal hole

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0