Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-435-7765

3a Firead Direction: Right-hand Thread Length: 0.032 inches Fastenr Length: Between 0.678 inches and 0.698 inches Head Heigh: Double hexagon extended washer Head Heigh: Between 0.248 inches and 0.268 inches Width Between Flats: 0.252 inches Extended Washer Diameter: Between 0.365 inches and 0.365 inches Extended Washer Thickness: 0.494 inches Between 0.365 inches and 0.365 inches Extended Washer Thickness: 0.494 inches Between 0.365 inches and 0.365 inches Between 0.365 inches and 0.365 inches Between 0.465 inches and 0.365 inches Between 0.465 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.395 inches Hole Quantity: 4 Hole Sumeer: 0.492 inches Hole Configuration Style: Dirled Hole Configuration Style: Dirled Between 0.165 inches/ Dirled inches <	
Right-hand Right-hand Thread Length: 0.092 inches Fastener Length: Between 0.678 inches and 0.698 inches Head Style: Double hexagon extended washer Head Style: Double hexagon extended washer Head Height: Between 0.248 inches and 0.268 inches Width Between Flats: 0.025 inches Between 0.365 inches and 0.268 inches Factended Washer Thickness: 0.040 inches Between 0.365 inches and 0.365 inches Factended Washer Thickness: 0.040 inches Between 0.421 inches and 0.052 inches Fist Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.190 inches Hole Type: Diffied Thready Cyp Per Inch (rpi): 32 Hole Confliguration Stype: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material Specificat	Thread Class:
Right-hand Thread Length: 0.092 inches Fastener Length: Between 0.678 inches and 0.698 inches Head Style: Double hexagon extended washer Head Height: Double hexagon extended washer Head Height: Between 0.248 inches and 0.268 inches Witth Between Flats: 0.025 inches Extended Washer Thickness: 0.026 inches Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Hole Diameter: Between 0.042 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Lengest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.190 inches Hole Countiy: 1 1026 inches Hole Speci Distance From Length 1025 inches Hole Countiy: 1 1026 inches Hole Speci Distance From Lengthexel 1027<	
Tread Length: 0.092 inches Fastener Length: Between 0.678 inches and 0.698 inches Head Style: Double hexagon extended washer Head Height: Between 0.248 inches and 0.268 inches Width Between Flats: 0.025 inches Kended Washer Diameter: Between 0.365 inches and 0.355 inches Extended Washer Thickness: 0.400 inches Hole Diameter: Between 0.162 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.052 inches First Diameter From Head: 0.402 inches Hole Quantity: 0.42 1.051 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.425 inches Hole Quantity: 4 Hole Configuration Style: Diable Configuration Style: Double hexagon longitudinal hole Extended Stop Diameter Countity: 1 Material Specification: Nickel alloy	
0.092 inclusion Fastener Length: Between 0.678 inches and 0.698 inches Head Height: Double hexagon extended washer Head Height: Between 0.248 inches and 0.268 inches Width Between Flats: 0.025 inches Extended Washer Diameter: Between 0.365 inches and 0.365 inches Extended Washer Thickness: 0.040 inches Hole Diameter: Between 0.462 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.052 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.190 inches Hole Quantity: 4 Hole Type: Dified Thready Oly Per Inch (tpl): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material Specification: Nickel alloy <td></td>	
Fastener Length: Between 0.678 inches and 0.698 inches Head Style: Double hexagon extended washer Head Netween 7 Between 0.248 inches and 0.268 inches Wicht Between Flats: 0.025 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Diameter: 0.040 inches Hole Diameter: Between 0.426 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Diates From Largest Bearing Surface Of Head To End Of First Diameter: 0.190 inches Hole Quantity: 4 Hole Type: Driled Thread Diameter: Diald Thread Diameter: Diald Diale Diale Hole Configuration Style: Diale First Diale Diale Hole Configuration Style: Diale First Diale First Diale	
Between 0.679 inches and 0.698 inches Head Style: Double hexagon extended washer Head Height: Between 0.248 inches and 0.268 inches Width Between Flats: 0.025 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Hole Diameter: Between 0.042 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.052 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Hole Quantity: 4 Hole Quantity: 10 Divide Extended Usper Inch (tpl): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material Specification: Nickel alloy Material Specification: Pow 96, cage 77445 mfr ref single material response	
Head Style: Double hexagon extended washer Head Height: Between 0.248 inches and 0.268 inches With Between Flats: 0.025 inches Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Hole Diameter: Between 0.426 inches and 0.352 inches First Diameter From Head: Between 0.426 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Hole Dype: 0.190 inches Hole Outpit: 4 Hole Outpit: 32 Hole Configuration Style: Dububle hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material Specification: Nickel alloy Material Specification: Piva 96, cage 77445 mfr ref single material response	-
Double hexagon extended washer Head Heigh: Between 0.248 inches and 0.268 inches Width Between Flats: 0.025 inches Extended Washer Diamter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Hole Diameter: Between 0.425 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.026 inches Hole Diameter: 0.190 inches Hole Quantity: 4 Hole Origination Style: Dilled Thready Ory Per Inch (tpi): 32 Hole Configuration Style: Dilled hexagon longitudinal hole Extendel Kalewei Body Diameter Quantity: 1 Material: Nickel alloy Material Specification: Pia Specification: Pia Specification:	
Head Height: Between 0.248 inches and 0.268 inches Width Between Flats: 0.025 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Hole Diameter: Between 0.42 inches and 0.52 inches First Diameter From Head: Between 0.45 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.190 inches Hole Diameter: 0.190 inches Hole Quantity: 4 Hole Type: Difiled Hole Type: Difiled Hole Configuration Style: Pace Indigueter Body Diameter Quantity: 1 Material: Nickel alloy Material: Nickel alloy Haterial Specification: Pay 96, cage 77445 mfr ref single material response	-
Between 0.248 inches and 0.268 inches 0.255 inches Extended Washer Diameter: Between 0.365 inches and 0.365 inches Extended Washer Thickness: 0.40 inches Bottowen 0.425 inches and 0.365 inches First Diameter: Between 0.42 inches and 0.052 inches First Diameter From Head: Between 0.455 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.190 inches Hole Quantity: 4 Hole Quantity: 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Nickel alloy Material Specification: Piva 96, cage 77445 mfr ref single material response	
Width Between Flats: 0.025 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Between 0.042 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.190 inches Hole Quantity: 4 Hole Quantity: 32 Pritead Oxf Per Inch (tpi): 32 Houe Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Nickel alloy Material Nickel alloy Piread Specification: Piva 96, cage 77445 mfr ref single material response	
0.025 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Hole Diameter: Between 0.042 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.190 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Nickel alloy Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	
Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.40 inches Hole Diameter: Between 0.42 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.25 inches Thread Diameter: 0.190 inches Hole Quantity: 4 Hole Type: Dillad Thready Oxy Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Extensily Relieved Body Diameter Quantity: 1 Nickel alloy Material: Nickel alloy Hoterial: Nickel alloy Hoterial: Nickel alloy Hoterial: Nickel alloy	
Between 0.385 inches and 0.385 inches Extended Washer Thickness: 0.404 inches Hole Diameter: Between 0.042 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.190 inches Hole Quantity: 4 Strined Prom Largest Descenter 0.190 inches Hole Type: Diffied Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Nickel alloy Material: Nickel alloy Haterial Specification: Pava 96, cage 77445 mfr ref single material response Thread Specification:	
Extended Washer Thickness: 0.040 inches Hole Diameter: Between 0.042 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.190 inches Hole Quantity: 4 Forst Days Diffied Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Nickel alloy Material: Nickel alloy Hoterali Pay 96, cage 77445 mfr ref single material response Thread Steise Designator:	
0.040 inchesHole Diameter:Between 0.042 inches and 0.052 inchesFirst Diameter From Head:Between 0.165 inches and 0.175 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.025 inchesThread Diameter:0.025 inchesHole Quantity:4Hole Type:DrilledThready Qty Per Inch (tpi):32Pouble hexagon longitudinal holeExternally Relieved Body Diameter Quantity:1Nickel alloyMaterial:Nickel alloyParael Singer TypesPiread Singer TypesPiread Singer Types1Piread Singer Types1Piread Singer Types1Piread Singer TypesPiread Singer TypesPirea	
Hole Diameter: Between 0.042 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.025 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	
Between 0.042 inches and 0.052 inches First Diameter From Head: Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.025 inches Thread Diameter: 0.190 inches Hole Quantity: 4 Hole Type: Drilled Thready Oty Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Nickel alloy Material: Nickel alloy Piva 96, cage 77445 mfr ref single material response Thread Sreise Designator:	
First Diameter From Head:Between 0.165 inches and 0.175 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.025 inchesThread Diameter:0.190 inchesHole Quantity:4Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:Double hexagon longitudinal holeExternally Relieved Body Diameter Quantity:1Nickel alloyPireial Specification:Piva 96, cage 77445 mfr ref single material responseFireed Series Designator:	Hole Diameter:
Between 0.165 inches and 0.175 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.025 inchesThread Diameter:0.190 inchesHole Quantity:4Hole Type:DrilledDrilledThready Qty Per Inch (tpi):32Hole Configuration Style:Double hexagon longitudinal holeExternally Relieved Body Diameter Quantity:1Nickel alloyMaterial:Nickel alloyPay 96, cage 77445 mfr ref single material responseThread Series Designator:	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:0.025 inchesThread Diameter:0.190 inchesHole Quantity:4Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:Double hexagon longitudinal holeExternally Relieved Body Diameter Quantity:1Nickel alloyMaterial:Nickel alloyPay 96, cage 77445 mfr ref single material responseThread Series Designator:	First Diameter From Head:
0.025 inches Thread Diameter: 0.190 inches Hole Quantity: 4 Hole Quantity: 1 Foready Qty Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	Between 0.165 inches and 0.175 inches
Thread Diameter:0.190 inchesHole Quantity:44Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:Double hexagon longitudinal holeExternally Relieved Body Diameter Quantity:1Material:Nickel alloyMaterial Specification:Pwa 96, cage 77445 mfr ref single material responseThread Series Designator:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.190 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response	0.025 inches
Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	Thread Diameter:
4 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response	
Hole Type:DrilledThready Qty Per Inch (tpi):32Hole Configuration Style:Double hexagon longitudinal holeExternally Relieved Body Diameter Quantity:1Material:Nickel alloyMaterial Specification:Pwa 96, cage 77445 mfr ref single material responseThread Series Designator:	Hole Quantity:
DrilledThready Qty Per Inch (tpi):3232Hole Configuration Style:Double hexagon longitudinal holeExternally Relieved Body Diameter Quantity:1Material:Nickel alloyMaterial Specification:Pwa 96, cage 77445 mfr ref single material responseThread Series Designator:	
Thready Qty Per Inch (tpi):32Hole Configuration Style:Double hexagon longitudinal holeExternally Relieved Body Diameter Quantity:1Material:Nickel alloyMaterial Specification:Pwa 96, cage 77445 mfr ref single material responseThread Series Designator:	
32 Hole Configuration Style: Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	
Hole Configuration Style:Double hexagon longitudinal holeExternally Relieved Body Diameter Quantity:11Material:Nickel alloyMaterial Specification:Pwa 96, cage 77445 mfr ref single material responseThread Series Designator:	
Double hexagon longitudinal hole Externally Relieved Body Diameter Quantity: 1 Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	
Externally Relieved Body Diameter Quantity: 1 Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	
1 Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	
Material: Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	Externally Relieved Body Diameter Quantity:
Nickel alloy Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	1
Material Specification: Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	Material:
Pwa 96, cage 77445 mfr ref single material response Thread Series Designator:	Nickel alloy
Thread Series Designator:	Material Specification:
	Pwa 96, cage 77445 mfr ref single material response
	Thread Series Designator:
Unjf	Unjf

NSN 5306-01-435-7765

Externally Relieved Body Bolt - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0