NSN 5306-01-435-7789

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand **Thread Length:**0.908 inches

Thread Direction:

Fastener Length:

Between 3.018 inches and 3.048 inches

За



View Online at https://aerobasegroup.com/nsn/5306-01-435-7789

Head Style:
Spline extended washer
Head Height:
Between 0.440 inches and 0.460 inches
Extended Washer Diameter:
Between 0.922 inches and 0.932 inches
Extended Washer Thickness:
Between 0.062 inches and 0.082 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Head Minor Diameter:
Between 0.644 inches and 0.651 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 2.115 inches and 2.135 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
220000 pounds per square inch Minimum Yield Strength:
Minimum Yield Strength:
Minimum Yield Strength: 125000 pounds per square inch
Minimum Yield Strength: 125000 pounds per square inch Surface Finish:
Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches grip
Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches grip Special Features:
Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches grip Special Features: Flat countersunk in center of shank
Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches grip Special Features: Flat countersunk in center of shank Material:
Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches grip Special Features: Flat countersunk in center of shank Material: Nickel alloy 718
Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches grip Special Features: Flat countersunk in center of shank Material: Nickel alloy 718 Material Specification:
Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches grip Special Features: Flat countersunk in center of shank Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response
Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches grip Special Features: Flat countersunk in center of shank Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment:

NSN 5306-01-435-7789

Shear Bolt - Page 2 of 2



Surface	Treatment	Specification:
Juliace	HEAUHEIL	opecilication.

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0