NSN 5306-01-435-7790

Machine Bolt - Page 1 of 2

Between 3.268 inches and 3.298 inches

Thread Class:

Right-hand
Thread Length:
0.908 inches
Fastener Length:

Head Style:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-435-7790

| Spline extended washer |
|---|
| Head Height: |
| Between 0.440 inches and 0.460 inches |
| Extended Washer Diameter: |
| Between 0.922 inches and 0.932 inches |
| Extended Washer Thickness: |
| Between 0.062 inches and 0.082 inches |
| Grip Diameter: |
| Between 0.4985 inches and 0.4995 inches |
| Head Minor Diameter: |
| Between 0.644 inches and 0.651 inches |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| Between 2.365 inches and 2.385 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Minimum Yield Strength: |
| 125000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches grip |
| Special Features: |
| Flat countersunk center drilling of shank |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| |
| |

NSN 5306-01-435-7790

Machine Bolt - Page 2 of 2



| Surface Treatment Sp | pecification: |
|----------------------|---------------|
|----------------------|---------------|

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0