

View Online at <https://aerobasegroup.com/nsn/5306-01-436-7679>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.528 inches

Fastener Length:

Between 1.638 inches and 1.668 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.676 inches and 0.690 inches

Shoulder Diameter:

0.4516 inches and 0.4526 inches

Shoulder Length:

1.115 inches first shoulder and 1.135 inches first shoulder

Thread Diameter:

0.4375 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Minimum Yield Strength:

95000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4340 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or ams 6322 assn standard 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas6207 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.