

View Online at <https://aerobasegroup.com/nsn/5306-01-437-0077>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.626 inches

**Fastener Length:**

Between 1.799 inches and 1.829 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.312 inches and 0.327 inches

**Width Between Flats:**

Between 0.926 inches and 0.940 inches

**Shoulder Diameter:**

0.6386 inches first shoulder and 0.6396 inches first shoulder

**Shoulder Length:**

1.178 inches first shoulder and 1.198 inches first shoulder

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Minimum Yield Strength:**

95000 pounds per square inch

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4340 or steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or ams 6322 assn standard 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6210 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.